

HORIZONTAL SECTION



OPERABLE ALUMINUM LOUVER XC/XCF-230W-0

STANDARD SPECIFICATION

- CONST. - 6063-T5 EXTRUDED ALUMINUM, SCREWED ASSEMBLY
- FRAME - 2" X .75" X .062"(50.8MM X 19.1MM X 1.6MM) CHANNEL, BUTT CORNERS
- BLADES - 2" X .062"(50.8MM X 1.6MM), 2.38" (60.4MM) BLADE SPACING, OPEN TO 30°
- SEALS - DUAL DUROMETER VINYL BLADE TIP & 1.75" (44.4MM) STAINLESS STEEL SIDE SEALS
- SHAFTS - .19"(4.8MM) DIA. PLATED C.R. STEEL
- BEARINGS - .19"(4.8MM) NYLON BUSHINGS
- LINKAGE - IN AIRSTREAM ON INSIDE FACE, ROD TRAVEL 2"(50.8MM)
- FINISH - MILL ALUMINUM
- CONTROL - MANUAL WING NUT
- SIZE - MINIMUM 10"W X 10"H (254MM X 254MM)
MAXIMUM 24"W X 48"H (609.6MM X 1219.2MM)

OPTIONS


- FRAME - XCF-ADD FLANGE FRAME 1.5" (38.1MM), USING A 2.5" X .081" (63.5MM X 2.1MM) FLAT BAR
- BEARINGS - OILITE BRONZE BUSHINGS
- SCREEN - IN FRAME, SCREWED ON OUTSIDE FACE
- FINISH - BAKED ENAMEL, ANODIZED & OTHERS
- CONTROL - SPRING & CHAIN, MOTORIZED

TECHNICAL NOTES

MAX. REC. INTAKE VEL.- 625 FPM THROUGH FREE AREA
SHIPPING WEIGHT - APPROX. 4 LBS./SQ. FT.

LOUVERS ARE MANUFACTURED .5" (12.7MM) SMALLER THAN OPENING SIZE, UNLESS EXACT DIMENSIONS ARE STATED.

* FOR MORE INFORMATION, CONTACT OUR FACTORY *



XC-230W-0
VERTICAL SECTION

XCF-230W-0
VERTICAL SECTION

NOTES

APPROVAL

DATE:
PROJECT:
ENGINEER:
CUSTOMER:
DISTRIBUTOR:

XC-230W-0