




HORIZONTAL SECTION



STEEL LOUVER SC-445W SF-445W

STANDARD SPECIFICATIONS

- CONST. - FORMED GALVANIZED STEEL, WELDED ASSEMBLY
- FRAME - 4" X 1" X 16 GAUGE (101.5MM X 25.4MM X 1.6MM), CHANNEL UP TO 48" (1219.2MM), 4" X 1.5" X 16 GAUGE (101.6MM X 38.1MM X 1.6MM) OVER 48" (1219.2MM), BUTT CORNERS
- BLADES - 4" X 16 GA. (101.6MM X 1.6MM), SET AT 45°, 4.5" (114.3MM) SPACING, SUPPORTS AT 48" (1219.2MM) CENTERS
- SCREEN - .5" X .5" (12.7MM X 12.7MM) X 18 GA. GALVANIZED, SCREW FASTENED
- FINISH - MILL GALVANIZED
- SIZE - MINIMUM 12" W X 12" H (304.8MM X 304.8MM)
 MAXIMUM SECTION WIDTH 72" (1828.8MM)
 MAXIMUM SECTION HEIGHT 120" (3048MM)
 MAXIMUM SECTION SIZE 40 SQ. FT.

OPTIONS

- CONST. - CONTINUOUS BLADE
- FRAME - SF - FLANGE FRAME 2" X 16 GAUGE (50.8MM X 1.6MM) STEEL ANGLE, MITERED CORNERS
- SCREEN - AS PER REQUEST
- FINISH - MINIMUM PRIME COAT OR BAKED ENAMEL IS RECOMMENDED

TECHNICAL NOTES


CORROSION RESISTANCE IS LOST UPON WELDING, SEE OPTIONAL FINISHES

MAX. REC. INTAKE VEL. - 725 FPM THROUGH FREE AREA

SHIPPING WEIGHT - APPROX. 8 LBS./SQ. FT.

LOUVERS ARE MANUFACTURED .5" (12.7MM) SMALLER THAN ORDERED SIZE UNLESS EXACT DIMENSIONS ARE STATED

* FOR MORE INFORMATION, CONTACT OUR FACTORY *



SC-445W
VERTICAL SECTION

SF-445W
VERTICAL SECTION

NOTES


APPROVAL

DATE:
PROJECT:
ENGINEER:
CUSTOMER:
DISTRIBUTOR:


SC-445W



STEEL LOUVER SC-445W




TEST
CONDITIONS:
A 48" X 48"
LOUVER WAS
USED FOR
THE TEST
AT STANDARD
AND
OPERATING
TEMPERATURE
RANGE OF
65°F - 85°F,
AND
15 MINUTES
TEST DURATION
WATER PENETRATION



		WIDTH (INCHES)										
HEIGHT (INCHES)		12	18	24	30	36	42	48	54	60	66	72
	12	0.15	0.25	0.34	0.44	0.53	0.62	0.72	0.81	0.91	1.00	1.10
16	0.30	0.49	0.68	0.87	1.06	1.25	1.44	1.63	1.82	2.01	2.20	2.40
20	0.43	0.69	0.96	1.22	1.46	1.76	2.02	2.29	2.55	2.82	3.08	3.35
24	0.51	0.83	1.15	1.47	1.79	2.11	2.42	2.74	3.06	3.38	3.70	4.02
28	0.65	1.05	1.46	1.86	2.27	2.67	3.08	3.48	3.89	4.29	4.69	5.09
32	0.76	1.23	1.70	2.18	2.65	3.12	3.60	4.07	4.54	5.01	5.49	5.96
36	0.91	1.48	2.05	2.61	3.18	3.75	4.32	4.88	5.45	6.02	6.59	7.16
40	1.03	1.68	2.32	2.97	3.61	4.25	4.90	5.54	6.19	6.83	7.47	8.11
44	1.12	1.82	2.51	3.21	3.91	4.60	5.30	6.00	6.69	7.39	8.09	8.79
48	1.26	2.04	2.82	3.60	4.39	5.17	5.95	6.74	7.52	8.30	9.09	9.87
52	1.37	2.22	3.07	3.92	4.77	5.62	6.47	7.32	8.18	9.03	9.88	10.73
56	1.52	2.46	3.41	4.35	5.30	6.25	7.19	8.14	9.08	10.03	10.98	11.93
60	1.64	2.66	3.69	4.71	5.73	6.75	7.78	8.80	9.82	10.84	11.87	12.89
64	1.73	2.80	3.88	4.95	6.03	7.10	8.18	9.25	10.33	11.40	12.48	13.55
68	1.86	3.02	4.19	5.35	6.51	7.67	8.83	9.99	11.15	12.31	13.48	14.64
72	1.97	3.20	4.43	5.66	6.89	8.12	9.35	10.58	11.81	13.04	14.27	15.49
76	2.12	3.45	4.77	6.10	7.42	8.75	10.07	11.41	12.72	14.04	15.37	16.69
80	2.25	3.65	5.05	6.45	7.85	9.25	10.65	12.05	13.45	14.85	16.26	17.66
84	2.33	3.79	5.24	6.69	8.15	9.60	11.05	12.51	13.96	15.42	16.87	18.32
88	2.47	4.01	5.55	7.09	8.63	10.17	11.71	13.25	14.79	16.33	17.87	19.41
92	2.58	4.19	5.80	7.40	9.01	10.62	12.23	13.84	15.44	17.05	18.66	20.26
96	2.73	4.43	6.14	7.84	9.54	11.24	12.95	14.66	16.35	18.05	19.76	21.46
100	2.85	4.63	6.41	8.19	9.97	11.75	13.53	15.20	16.90	18.60	20.30	22.00
104	2.94	4.77	6.60	8.44	10.27	12.10	13.93	15.74	17.44	19.14	20.84	22.54
108	3.08	4.99	6.91	8.83	10.75	12.67	14.58	16.38	18.18	19.98	21.78	23.58
112	3.19	5.17	7.16	9.15	11.13	13.12	15.10	16.98	18.86	20.74	22.62	24.50
116	3.34	5.42	7.50	9.58	11.66	13.74	15.82	17.79	19.68	21.57	23.46	25.35
120	3.46	5.62	7.78	9.93	12.09	14.25	16.41	18.27	20.16	22.05	23.94	26.83

FREE AREA TABLE (SQUARE FEET)
RATING INCLUDES THE EFFECT OF A BIRDSCREEN



THE INFORMATION CONTAINED ON THIS DATA SHEET REMAINS THE PROPERTY OF WESTERN VENTILATION PRODUCTS LTD. AND IS PROTECTED BY COPYRIGHT. WESTVENT AIR PERFORMANCE RATINGS SHOWN ARE BASED ON TESTS MADE BY TECHNICIANS IN OUR TEST LABORATORY.